



Safes for every application
Commercial, Residential or Small Businesses



PREMIUM QUALITY SAFES YOU CAN TRUST



THE FINEST FIRE AND BURGLARY PROTECTION AVAILABLE ANYWHERE IN THE WORLD!

Gardall designs and manufactures fire and burglary resistive safes to meet or exceed many different standards and specifications.

Standard Safe Classifications

To understand how our safes are classified, here is a brief explanation of the labels you'll find on them.

Fire Protection – Two-Hour 1850° or One-Hour 1700°

Gardall fire-resistive safes meet or exceed Underwriters' Laboratories specifications for explosion, fire endurance and drop tests.

Two-Hour exposure to severe fire with an exterior temperature to 1850°F, and an interior temperature that does not exceed 350°F (paper chars at 405°F) for two hours and cool down.



One-Hour exposure to severe fire with an exterior temperature to 1700°F, and an interior temperature that does not exceed 350°F (paper chars at 405°F) for one hour and cool down.



Residential Security Container

Both the GBF series and the FB series of safes carry the U.L.-R.S.C. burglary label.



Burglary Protection

Gardall safes with the Class "B" or Class "C" Burglary Insurance Rating allow you to receive insurance coverage in accordance with the Broad Form and Mercantile Safe Insurance classifications. Pertinent insurance information is available from Insurance Service Office, 160 Water Street, New York, NY 10038.

Gardall safes can be supplied with an Underwriters' Laboratory Group II combination lock, U.L. listed key-op lock, U.L. listed dual key lock or a U.L. listed push button electronic lock.

Your Lifetime Gardall Warranty


Gardall Safe Corporation assures to the original end consumer, replacement – free of charge – of any Gardall Fire-Resistive Record Safe damaged beyond repair by fire with a then-current production model of a comparable value. This warranty is exclusive and in lieu of any warranty of merchantability, fitness for particular purpose or other warranties of qualities, whether expressed or implied, and of all other liabilities and obligations on the manufacturer's part.

Gardall Safe Corporation reserves the right to inspect any record safe prior to replacement. Copies of insurance reports or documents pertaining to fire loss will be furnished to Gardall Safe Corporation upon request.

Gardall Safe Corporation specifically assumes no liability for installation or other charges incurred by the owner in connection with the replacement of any record safe and assumes no liability for damage to contents or personal property contained in any such file or any consequential damages of any nature or description.

Pictures & Specifications

U.L. Two-Hour Fire Safes – Small and Medium Sizes _____	2
Large Two-Hour Fire Safes _____	3
U.L. Burglary Rated/One-Hour Fire Safes – BF Series _____	4
Data-Media Safes _____	5
One-Hour Microwave Fire Safes _____	6
U.L. One-Hour Fire / Burglary Safes _____	7
Economical Two-Hour Record Safes _____	8
Single Door Depositories – Rotary, Front and Back Loading _____	9
Double Door Depositories – Rotary and Front Loading _____	10
Economical Depository Safes – “B” Rated _____	11
Cash Register Tray /Wide Body Depositories _____	12
Commercial In-Floor Safes _____	13
Under Counter Depositories / Utility “B” Rated Safe _____	14
“B” Rated Money Chests _____	15
Concealed Wall Safes – Heavy Duty, Regular and Insulated _____	16
Firelined Gun/Pistol Safes _____	17
Dual Security – “B” Rated Safe within a Two-Hour Fire Safe and Safe Chest Combination – TL15 /U.L. Two-Hour Fire Safe _____	18
Commercial High Security – TL15, TL30 and TL30X6 _____	19
In-Room Safe (Hotel, Hospital, Residence Hall) _____	20





**Gardall's New Two-Hour Safes,
with the Most Features in the Industry**

Visit us online at
www.gardall.com
MADE IN THE U.S.A.

Can Your Business or Home Office Survive Record Losses From Fire?

Statistics show that if a company's records are lost in a fire, 17% can no longer furnish a financial statement, 14% suffer a reduction in credit rating and 43% go out of business completely. No home or business is safe from fire. Your vital records and possessions are only as safe as the quality of protection you provide for them. With Gardall fire resistive safes, you can be confident your records will survive.



Standard Features

- Thick 4¼" door with recessed anti-pry design. Safe walls are 2½" thick
- Five active bolts that lock in 3 directions, massive 1" diameter round bolts that extend deep into safes body (Models 1812-3018)
- Center bolt down hole with hardware included for easy installation (hardware included)
- Plush carpeted quality interior to protect jewelry and valuables (Models 1812-3018)
- UL listed Group II high security lock, mechanical or electronic available
- UL 2-hour fire label, furnace-tested to 1850°F for 2 hours. Interior temperature of safe was less than 350°F during the test and cool down

- Solid chrome-plated handle with shear point to prevent the safe from being forced open by handle attack
- Independent re-locker and hardplate to prevent drilling attack on locking mechanism
- **Lifetime Replacement Guarantee** (see inside front cover)

Options

- Key locking dial
- Custom Paint with Gold trim – rich color exteriors (Black, Burgundy, or Hunter Green)

Standard colors: Sandstone or Gray.

All specifications are subject to change without notice. The above mentioned Gardall fire resistive safes carry a U.L. 2 hour 350° fire label as to Fire and Impact tests.



Model	Outside Dimensions			Inside Dimensions			Cubic Inches	Weight (lbs.)	Shelves
	H	W	D	H	W	D			
1411/2	21¼"	16¼"	18¾"	14"	11"	10¼"	1579	248	0
1612/2	23¼"	17¼"	19¾"	16"	12"	11¾"	2256	298	1
1812/2	25"	17¼"	19¾"	18"	12"	11¾"	2538	313	1
1818/2	25"	17¼"	25¾"	18"	12"	17¾"	3834	392	1
171718/2	25"	23¼"	25¾"	18"	18"	17¾"	5751	487	2
2218/2	29¼"	23¼"	25¾"	22"	18"	17¾"	7029	525	2
3018/2	37¼"	23¼"	25¾"	30"	18"	17¾"	9585	620	3

Add 2" to outside depth for dial and handle.



**Your Best Protection
Against Fire or Theft**

Visit us online at
www.gardall.com
MADE IN THE U.S.A.

Large Two-Hour Fire Safes

These Gardall fire resistive safes are designed and tested to withstand severe fire with outside temperatures reaching 1750°F for two hours. Safe interior temperatures will not exceed 350°F within two hours. The charring of paper occurs at 405°F. All Gardall fire resistive safes provide a comfortable margin that protects your valuables. But these models don't stop at just fire protection. They also



have Class "B" burglary resistive features built in right at the factory. And don't forget, every fire insurance policy states that "proof of loss" is required for claims. When your business or personnel inventories are locked inside a Gardall fire resistive safe, your "proof of loss" is protected 24 hours a day, 7 days a week.

Standard Features

- Full locking bar on hinged side of door deterring entry by removal of hinges
- Plated interlocking door bolts extend into safe wall preventing entry if hinges are removed.
- Hard plate between the lock and dial ring.
- Independent locking device designed to stop forced entry
- U.L. group II combination or electronic push-button lock available.
- Heavy duty casters to allow the safe to be positioned easily (welded on)

Manufacturers 2-Hr. Fire Label

A safe similar in construction was tested by an independent testing facility. The furnace temperature reached 1750°F for a period of time exceeding 2 hrs., before the interior of the safe reached 350°F.

Lock Options

- Push Button Electronic
- Mechanical Combination
- Single Key (Key-op)

Standard colors: Gray or sandstone.

The above mentioned Gardall fire resistive safes carry a 2-hour Manufacturers Fire Label.

All specifications are subject to change without notice.

Model	Outside Dimensions			Inside Dimensions			Cubic Inches	Approx. Weight (lbs.)	Shelves
	H	W	D	H	W	D			
3620	43½"	25¾"	26¾"	36¾"	20½"	19½"	14,490	804	3
4220	49½"	25¾"	26¾"	42¾"	20½"	19½"	16,890	875	3
4820	55½"	25¾"	26¾"	48¾"	20½"	19½"	19,285	975	4

Add 2" to outside depth for dial and handle.



**Your Best Protection
Against Fire and Burglary**

Visit us online at
www.gardall.com
MADE IN THE U.S.A.

All GBF safes were tested by the manufacturer along side a U.L. listed one-hour fire safe in an independent fire testing facility. The GBF safe actually outperformed the U.L. fire safe by 15 minutes. The exterior of the safe was heated to 1700°F for one hour and during that time the interior temperature of the safe was less than 270°F. A letter of certification is available upon request. All GBF safes carry Gardall's Lifetime Replacement Guarantee.



Gardall's GBF models provide both burglary and fire protection for your home or office application. We have been manufacturing fire safes since 1950 and the GBF safe is our premier model in quality and function.

Standard Features

- **Door:** 1½" profile door panel with overall 4" thickness, insulated for protection against fire, with a "B" burglary rating.
- **Body:** 1/8" plate steel with 2½" of insulation and a metal inner shell.

Anti Burglary Components:

- Hard plate to deter drilling.
- Independent re-locking device.
- Solid steel handle designed to shear off under attack.
- Three massive 1" round chrome plated locking bolts.
- Full length locking bar on hinge side of safe deterring prying attacks.
- One anchoring hole in base for easy bolt down. (hardware included)
- **Lifetime Replacement Guarantee**
- Intumescent seal to ensure a positive door seal in case of fire.

Fire and Burglary Labels

- U.L. Residential Security Container Burglary Label (RSC)
- Manufacturer's 350° 1 Hour Fire Label

Lock Options

- Electronic, Combination, Single Key
- Standard colors:* Gardall Gray or Sandstone.

Deluxe Option

- Gold handle, dial and trim.

Optional Color:
Black, hunter green, maroon

** Intumescent means an expandable door seal meant to protect your valuables from fire, smoke, and water damage.*



Model	Outside Dimensions			Inside Dimensions			Cubic Inches	Approx. Weight (lbs.)	Shelves
	H	W	D	H	W	D			
GBF1713	21¼"	18½"	20½"	16½"	13"	13¼"	2,842	355	1
GBF2016	25¼"	21¼"	22½"	20"	16½"	15¼"	5,032	467	1
GBF3318	38¼"	23"	26¼"	33"	17¼"	18"	10,246	796	2

Add 2" to outside depth for dial and handle.



**Your Best Protection for
Media Against Fire or Theft**

Visit us online at
www.gardall.com



With the growing number of homes and offices using computers, the protection of magnetic media has become extremely critical. The loss of personal as well as business records can be costly and devastating. The average fire safe is not designed to protect your electronic records. Gardall's media safes are designed to meet the additional requirements of protecting magnetic media. For your convenience we offer two sizes to choose from.

Standard Features

- Push button electronic lock with key day lock
- 3 way bolt work with bolt detent and 5 active bolts
- Push button electronic lock – 6-digit combo
- One removable shelf
- No anchoring holes
- Key operated day lock

Protect Your Electronic Media

- Office Computer Back-Ups
- Home Computer Back-Ups
- Digital Pictures
- Music CDs
- DVDs
- Video Tapes
- One-hour fire protection for media products

Model	Outside Dimensions			Inside Dimensions			Approx. Weight (lbs.)	Shelves
	H	W	D	H	W	D		
EDS-1210-G-EK	21½"	19½"	18½"	11"	9"	7¾"	209	1
EDS-2214-G-EK	31½"	23¾"	20"	20¾"	12½"	8"	374	2

Add 1½" to outside depth for dial and handle. No bolt-down hole in these models.



Gardall Microwave Safes...
Premium Quality You Can Trust

Visit us online at
www.gardall.com

Gardall offers a full range of U.L. approved fire resistive microwave style safes. These safes are made to Gardall's exact specifications and brought to you with the same care and quality you have come to expect from Gardall. Microwave style safes come with either mechanical or electronic style locks. All fire safes have plated interlocking bolts that extend into the safe walls to prevent tampering and removal of doors. The doors are precision built of extra heavy steel, full swinging on heavy duty hinges with interlocking, tongue and groove closure on all sides of the door frame. All safes come with a center bolt down hole and hardware to anchor the safe down.



Microwave Safes

- One-hour fire safe label*
- Two compact sizes
- Center bolt down (hardware included)
- Dual security key and combination (mechanical only)
- Programmable electronic lock with over-ride code
- Individual packaging for UPS type shipping
- Powder coated paint for increased durability
- Pull-out tray for storage of small items
- Gardall warranty for all products

Model	Outside Dimensions			Inside Dimensions			Approx. Wt. (lbs.)	Description
	H	W	D	H	W	D		
MS911-G-CK	11½"	15¼"	12½"	8½"	12"	8½"	61	Horizontal 1 Hr Fire Safe with Combination Lock
MS911-G-E	11½"	15¼"	12½"	8½"	12"	8½"	61	Horizontal 1 Hr Fire Safe with Electronic Lock
MS119-G-CK	15½"	11¾"	12½"	12¼"	8¾"	8½"	61	Vertical 1 Hr Fire Safe with Combination Lock
MS119-G-E	15½"	11¾"	12½"	12¼"	8¾"	8½"	61	Vertical 1 Hr Fire Safe with Electronic Lock
* MS912-G-CK	13½"	16¾"	15¼"	9½"	12¾"	10¼"	85	Horizontal 1 Hr Fire Safe with Combination Lock
* MS912-G-E	13½"	16¾"	15¼"	9½"	12¾"	10¼"	85	Horizontal 1 Hr Fire Safe with Electronic Lock
* MS129-G-CK	16¾"	13½"	15¼"	12¾"	9½"	10¼"	85	Vertical 1 Hr Fire Safe with Combination Lock
* MS129-G-E	16¾"	13½"	15¼"	12¾"	9½"	10¼"	85	Vertical 1 Hr Fire Safe with Electronic Lock

* U.L. 350° One-Hour Label – Fire and Impact Test Add 1½" to outside depth for dial and handle.



**One-Hour Gardall Safes...
Premium Quality You Can Trust**

Visit us online at
www.gardall.com

U.L. One-Hour Fire/Burglary Safes



Gardall's FB series safes are the next higher level of protection after our U.L. two-hour series safes. They have easily passed both the U.L. Fire and U.L.-R.S.C. tests.

Fire/Burglary Safe Standard Features

- Heavy duty construction 2" thick door, 3" thick body
- Composite construction door & body
- Independent glass re-locking system
- 3 spoke chrome plated vault handle
- 1 Hour U.L. 350° fire label
- U.L. RSC Burglary Label

- Center bolt down for ease of installation (hardware included)
- 1¼" chrome plated locking bolts
- Attractive two tone paint for increased durability
- U.L. Group II combination (S&G) lock standard

Lock Options

- U.L. electronic or key-op lock

Model	Outside Dimensions			Inside Dimensions			Cubic Inches	Approx. Weight (lbs.)	Shelves
	H	W	D	H	W	D			
FB-1212	17¾"	17¾"	20½"	12"	12"	12¾"	1836	205	1
FB-2013	27"	20"	20½"	21¼"	14¼"	13"	3523	312	2
FB-2714	33½"	20"	22¾"	27½"	14⅞"	15¼"	5982	412	2

Add 2" to outside depth for dial and handle.



Two-Hour Gardall Safes...
Premium Quality You Can Trust

Visit us online at
www.gardall.com



Economical Two-Hour Record Safes

Gardall offers a full range of two-hour record safes, for residential or commercial use. All five models are available with an attractive two-tone glossy finish. All models carry a KIS two-hour fire label and in addition, the Model 1612 carries a UL 350°F One-Hour label (fire and impact tests).

Standard Features (Models 1913-4422)

- S&G Group II combo lock
- 3 way bolt work (5 active bolts)
- Day lock
- Pull out inner key locking compartment
- U.L. 350° one-hour fire label on Model 1612
- Center bolt down hole with hardware included
- KIS Fire Test – Extreme furnace temperature up to 1832°F for two hours. The interior of the safe was not damaged and only rose to 232°F for a high temperature

Model	Outside Dimensions			Inside Dimensions			Approx. Weight (lbs.)
	H	W	D	H	W	D	
*SS1612-G-CK	20"	16¼"	17½"	14½"	12¼"	14¾"	140
*ES1612-G-E	20"	16¼"	17½"	14½"	12¼"	14¾"	140
SS1913-G-CK▲	25¼"	19¼"	18¼"	18¾"	12½"	11¼"	210
SS2517-G-CK▲	31¼"	23¼"	25"	24¾"	16⅝"	13¼"	352
SS3918-G-CK▲	46½"	25½"	25¼"	35⅝"	18¾"	17¾"	592
SS4422-G-CK▲	50¾"	29¼"	25¼"	39½"	22½"	17½"	805

* U.L. 350° One-Hour Label – Fire and Impact Test

▲ S&G mechanical lock standard Add 1½" to outside depth for dial and handle.



Gardall's Single Door Depositories

Visit us online at
www.gardall.com



Designed to protect money collection where immediate deposit is required. Deposit can be made into the safe while the door is locked. Exclusive baffle design prevents contents from being removed through the entry opening. Hopper rotor is built into safe body and cannot be removed to gain access to the safe.

Heavy Duty Depositories Standard Design Benefits

- CLASS B Insurance Rating – 1/2" steel door with punch resistant bolt and relocking device to deter forcible entry. 1/4" steel body construction.
- Dual Custody Key Locks – Requires 2 keys to open door for absolute security.
- Finest quality U.L. Group II S&G combination lock – Key changeable combination, capable of 1 million possible choices.
- Triple boltwork with independent relocking device.
- Relocking device – If back cover is knocked off of lock, the independent relock device is activated, preventing bolt withdrawal. Available on either combination or dual key operated doors.
- Rotary Hopper Capacity – 3¾" x 9" x 4" designed to fit most standard money bags and envelopes.

- Front Loading Capacity – designed to fit most large money bags – 2¾" x 10½" x 7½"
- Interchangeable Doors – 2 sizes 9" x 9" and 12" x 12"
- 4 anchoring holes in base.

Standard color: Gray

All specifications are subject to change without notice.

To Operate Rotary Hopper

Drop contents into the rotor drum, turn rotor slowly (DO NOT SPIN). Check drum to be certain contents have dropped.

To Operate Front Loading Depository

Pull drop door forward, place items to be deposited inside, release the drop door. Deposited item should drop inside. Open the drop door to be certain.

Model	Outside Dimensions			Inside Dimensions			Inside Cubic Inches	Approx. Weight (lbs.)
	H	W	D	H	W	D		
RC-1218	18"	11½"	13"	11"	10½"	10½"	1213	105
RC-1228	25"	14½"	13"	17"	13¾"	11½"	2688	160
FL-1218	18"	11½"	13"	11"	10½"	10½"	1213	110
FL-1328	25"	14½"	13"	15¼"	13½"	11¼"	2329	165
BL-1328	25"	14½"	13"	15¼"	13½"	11¼"	2329	150

Above available as (K) dual key lock (C) Group II combination lock, (KO) key-op lock or (ZE/LCE) electronic lock. Please specify.

*BL designates depository on back side of safe from door. Add 2" to outside depth for dial and handle.

IMPORTANT! These safes are built with the intent of keeping large bills and valuables out of unprotected areas, until deposits can be made. They are not meant to be used as unprotected storage safes for overnight, or lengthy periods of time. Discuss your need with your local safe professional or if you are in doubt, call GARDALL and we will recommend a safe expert.



**Your Best Protection
Against Robbery**

Visit us online at
www.gardall.com



Not intended for overnight storage of large amounts of cash. Make bank deposits frequently.

All specifications are subject to change without notice.

Rotary and Front Loading Depositories

- **RC-1237K-FL/BL-1337K**
Both doors with dual key lock.
- **RC-1237C-FL/BL-1337C**
Both doors with Group II combination locks or key-op locks.
- **RC-1237KC-FL/BL-1337KC**
Top door dual key lock. Bottom door Group II combination lock or key-op lock.
- **RC-1237CK-FL/BL-1337CK**
Top door Group II combination lock or key-op lock. Bottom door dual key lock.

Standard Design Features

- "B" rated double door depository. Top compartment designed for drop area.
- Bottom compartment for storage of valuables or small amounts of change.
- For more capacity either mode can be furnished with only one door using the entire inside for the drop area. (Single door top or bottom).
- Interchangeable doors – key operated doors will change to combination lock door with ease.
- FL opening 2 $\frac{3}{4}$ " x 10 $\frac{1}{2}$ " x 7 $\frac{1}{2}$ "

*Available with electronic push-button lock
Standard color: Gray*

Model	Outside Dimensions				Inside Dimensions			Inside Cubic Inches	Door Size	Approx. Weight (lbs.)
	H	W	D	T	H	W	D			
RC-1237	36 $\frac{3}{4}$ "	14 $\frac{1}{2}$ "	13"	T	14 $\frac{3}{4}$ "	13 $\frac{3}{4}$ "	10 $\frac{3}{4}$ "	2180	12"x12"x1/2"	220
				B	14 $\frac{3}{4}$ "	13 $\frac{3}{4}$ "	10 $\frac{3}{4}$ "	2180		
FL-1337	36 $\frac{1}{2}$ "	14 $\frac{1}{2}$ "	13"	T	12"	13 $\frac{1}{2}$ "	10 $\frac{3}{4}$ "	1848	12"x12"x1/2"	215
				B	13 $\frac{3}{4}$ "	13 $\frac{3}{4}$ "	10 $\frac{3}{4}$ "	2032		
*BL-1337	36 $\frac{1}{2}$ "	14 $\frac{1}{2}$ "	13"	T	12"	13 $\frac{1}{2}$ "	10 $\frac{3}{4}$ "	1848	12"x12"x1/2"	215
				B	13 $\frac{3}{4}$ "	13 $\frac{3}{4}$ "	10 $\frac{3}{4}$ "	2032		

Safes available as (K) dual key lock (C) Group II combination lock, (KO) key-op lock or (ZE) electronic lock. Please specify.

*BL designates depository on back side of safe from door. Add 2" to outside depth for dial and handle.



**Economical Gardall Safes...
Premium Quality You Can Trust**

Visit us online at
www.gardall.com

Economical Depository Safes



Economical Depository Safes

Front Loading Depository Safes

Single Door

- "B" rated solid 1/2" thick steel door 1/4" body
- 3 active locking bolts
- Anchoring holes for ease of installation
- Anti fish baffles
- Electronic welding for strength
- UL Group II combination lock (S&G)
- Powder coated paint for durability

Double Door

- Solid steel locking bar to prevent door removal
- Front load style for added security and ease of deposits
- Electronic welding for strength and durability
- Powder coated paint for durability

Standard Features

- 1/2" plate steel door
- 1/4" thick body
- External re-locker
- Anti fish sawtooth baffle
- Excellent for mounting in delivery vehicles
- Mounting holes pre-drilled
- Available in 3 sizes
- Laser cut door for exact fit

Model	Outside Dimensions			Inside Dimensions			Weight (lbs.)	
	H	W	D	H	W	D		
DS-1914-G-C★	19"	13½"	15"	12"	12¾"	12"	128	
DS-3315-G-CC★	32¼"	15¾"	15¾"	10¼"	12½"	14½"	237	
DS-3315-G-EE	32¼"	15¾"	15¾"	10¼"	12½"	14½"	237	
DS-3920-G-CC★	39"	20¼"	22"	Top	12½"	19½"	19¼"	374
				Bottom	12½"	19½"	19¼"	

Add 1½" to outside depth for dial and handle. ★S&G mechanical locks standard.



Your Best Protection
Against Robbery

Visit us online at
www.gardall.com



Keep your cash register trays secure when they are not being used. Reduce petty theft and loss from out of balance cash drawers. Available in three sizes.

Standard Features

- Recessed door to help deter pry attacks.
- Hard plate around the lock, with independent relocker.
- Available with Rotary or Front Loading depository.
- Interiors – 2 adjustable shelves or 5 fixed shelves.
- S&G Group II combination lock
- Anchoring holes in bottom to bolt safe down.
- 3–1" round bolts and full length dead bolt.
- Inside compartment 9"H x 21"W x 13"D (FL & WB models)
- 1/2" plate steel door on Model 3522 and 3020

Model	Outside Dimensions			Interior	H	W	D	Weight
	H	W	D					
FL-2522/2	33¼"	22"	17"	Drop compartment with cam lock				259
FL-2522/5	33¼"	22"	17"	2 adjustable, removable shelves				
DS-3020-G-C •	30"	20"	20"	Drop compartment with cam lock	12¼"	19½"	17½"	233
				5 fixed location, removable shelves	7"	19½"	16"	
GWB-3522 •	35"	21¾"	16½"	Inside Comp.				233
				Drop compartment with cam locks and 2 shelves, 1/2" plate steel door				307

• "B" rate construction Add 2" to outside depth for dial and handle.


FL/RC compartment size 5½" x 21½" x 10½". GWB compartment size 8½" x 21¾" x 10½"



**Your Best Protection
Against Robbery**

Visit us online at
www.gardall.com

Larger/Improved • Lower Cost • Quality Construction



In floor safes are designed to be buried in the floor and concealed by a dust cover under a rug or carpet. Installation should be done by a professional safe dealer.

Standard Features

- Group II U.L. listed combination or electronic push-button locks.
- Hard plate between the lock and dial ring.
- Full length locking bar hinge side of door.
- Independent relocking device to deter forced entry.
- Door frame is reinforced on bolt side.
- Coil spring assist on all doors for ease of opening and closing.
- Dust cover included.
- "B" rate burglary construction.
- 5 active 3/4" bolts.

Commercial In-Floor Safes

Model	Outside Dimensions			Inside Dimensions			Inside Cubic Inches	Approx. Wt. (lbs.)	Door Size
	H	W	D	H	W	D			
B-1307	14¾"	12⅞"	11¼"	13¾"	12½"	8"	1375	100	12"x12"x1/2"
B-1311	14¾"	12⅞"	16¼"	13¾"	12½"	13"	2234	117	12"x12"x1/2"
G-3600	23½"	12½"	17¼"	22¾"	12"	13½"	3686	150	12"x12"x1/2"

Square Tube Safe with Liftout Head

Model	Outside Dimensions			Inside Dimensions			Inside Cubic Inches	Approx. Wt. (lbs.)	Door Size
	H	W	D	H	W	D			
G500	8"	8"	11¼"	7⅝"	7⅝"	7¼"	523	42	7½"x7½"x1/2"
G700	8"	8"	15¼"	7⅝"	7⅝"	11¾"	755	51	7½"x7½"x1/2"

Standard color: Gray. All specifications are subject to change without notice.



**Your Best Protection
Against Robbery**

Visit us online at
www.gardall.com



Keep excess till cash locked away and out of sight to prevent loss from pilferage.

Under Counter Depository Safes – 1/2" Plate Steel Door, 1/4" Body

Model	Outside Dimensions			Inside Dimensions			Weight (lbs.)
	H	W	D	H	W	D	
DS-86-G-K	8"	6"	12"	7½"	5½"	11"	34
DS-86-G-C	8"	6"	12"	7½"	5½"	11"	34
TC-1206-G-K	12"	6½"	6"	9¼"	6"	4½"	35
TC-1206-G-C	12"	6"	8"	10⅞"	4¾"	7"	35
DS-1210-G-K	12"	8"	10"	10¼"	7½"	9"	47
DS-1210-G-C	12"	8"	10"	10¼"	7½"	9"	47

Anchoring holes in bottom for easy installation



Compact Utility Safes

Designed for use in walls, basements, car trunks, and RV's. Solid steel plate with insurance "B" rated construction. This safe also features a U.L. listed Group II combination lock. Door will interchange with many other Gardall Safes. 1/2" pre-drilled mounting holes in base.

Standard Features

- 1/2" plate steel door
- Independent relock on lock
- Group II electronic lock (optional)
- S&G combo lock standard
- 4 anchoring holes in bottom

Model	Outside Dimensions			Inside Dimensions			Inside Cubic Inches	Approx. Weight (lbs.)
	H	W	D	H	W	D		
H-2	11¼"	11½"	12¾"	11"	11"	9¼"	1184	70

Add 1½" to outside depth for dial and handle.



**Your Best Protection
Against Robbery**

Visit us online at
www.gardall.com

"B" Rated Money Chests

These "B" rated burglary safes are great for commercial storage or home use. They feature laser cut 1/2" plate steel doors, large locking bolts and bolt down capability. Available in four different sizes.



Five massive 1/4" bolts in boltwork

Standard Features

- 1/2" plate steel door
- 1/4" steel body
- 5 active 1/4" locking bolts
- S&G Group II combination lock
- Heavy duty hinges
- Full length locking bar to deter prying attack on hinges
- 4 anchoring holes in bottom
- 1 adjustable shelf

Lock Options

- 6 digit push button electronic lock, \$50.00 list extra
- Group II electronic locks, \$225 list extra

Model	Outside Dimensions			Inside Dimensions			Inside Cubic Inches	Weight (lbs.)
	H	W	D	H	W	D		
B-1515	15"	15 3/4"	12 1/4"	14 1/2"	15 1/4"	10 1/2"	2322	130
B-2015	20 1/2"	15 3/4"	18 1/4"	20"	15 1/4"	15 3/4"	4804	161
B-2018	21 1/4"	19 1/4"	22 3/4"	20 3/4"	18 3/4"	20 1/2"	7976	214
B-2815	28 1/2"	23 1/2"	17 3/4"	28"	22 1/2"	15"	8277	329
B-2818▲	30"	19"	23"	28"	18"	20"	10,080	271

1/2" steel plate door, 1/4" prime steel body ▲ Model 2818 has 2 shelves Add 2" to outside depth for dial and handle.



**Your Best Protection
Against Robbery**

Visit us online at
www.gardall.com



Heavy Duty Concealed Wall Safes

Wall safes have a 1" flange for easier installation. Designed to be recessed into a wall and concealed by a picture or a mirror. Available with U.L. Group II electronic lock as an option or without a flange. Available for 4" or 6" wall depth.

Model	Outside Dimensions			Inside Dimensions			Inside Cubic Inches	Approx. Weight (lbs.)
	H	W	D	H	W	D		
SL-4000	12 $\frac{3}{8}$ "	14 $\frac{3}{8}$ "	4"	12"	13 $\frac{1}{2}$ "	2 $\frac{3}{4}$ "	446	39
SL-4000/F	12 $\frac{3}{8}$ "	14 $\frac{3}{8}$ "	4"	12"	13 $\frac{1}{2}$ "	2 $\frac{3}{4}$ "	446	41
SL-6000	12 $\frac{3}{8}$ "	14 $\frac{3}{8}$ "	6"	12"	14"	4 $\frac{1}{2}$ "	756	45
SL-6000/F	12 $\frac{3}{8}$ "	14 $\frac{3}{8}$ "	6"	12"	14"	4 $\frac{1}{2}$ "	756	47

*Available with or without 1" flange. Shelf is not adjustable.



Concealed Wall Safes

Wall safes have a 1" flange for easier installation. Designed to be recessed into a wall and concealed by a picture or a mirror. Available with either a key operated lock or a 6 digit electronic and key lock for extra security. 3 active bolts in boltwork. Available for 4" or 6" wall depth.

Model	Outside Dimensions			Inside Dimensions			Weight (lbs.)
	H	W	D	H	W	D	
WS-1314-T-K or EK	13 $\frac{3}{4}$ "	14 $\frac{1}{2}$ "	4"	12"	14"	2 $\frac{1}{2}$ "	27
WS-1317-T-K or EK	13 $\frac{3}{4}$ "	14 $\frac{1}{2}$ "	5 $\frac{1}{2}$ "	12"	14"	3 $\frac{1}{2}$ "	30

Key required to open safe door. Shelf is not adjustable.



Insulated Wall Safes

We have four models of insulated wall safes. They come with a 2" flange and bolt down hardware to make installation easier. Safes are horizontal or vertical in design and have the same features as our Microwave Safes on page 6.

Model	Outside Dimensions			Inside Dimensions			Approx. Weight (lbs.)
	H	W	D	H	W	D	
WMS911-G-CK or E	11 $\frac{1}{2}$ "	15 $\frac{1}{4}$ "	12 $\frac{1}{2}$ "	8 $\frac{1}{2}$ "	12"	8 $\frac{1}{2}$ "	61
WMS119-G-CK or E	15 $\frac{1}{2}$ "	11 $\frac{1}{2}$ "	12 $\frac{1}{2}$ "	12 $\frac{1}{4}$ "	8 $\frac{1}{2}$ "	8 $\frac{1}{2}$ "	61
WMS912-G-CK or E*	13 $\frac{1}{2}$ "	16 $\frac{3}{4}$ "	15 $\frac{1}{4}$ "	9 $\frac{1}{2}$ "	12 $\frac{3}{4}$ "	10 $\frac{1}{4}$ "	85
WMS129-G-CK or E*	16 $\frac{3}{4}$ "	13 $\frac{1}{2}$ "	15 $\frac{1}{4}$ "	12 $\frac{3}{4}$ "	9 $\frac{1}{2}$ "	10 $\frac{1}{4}$ "	85

* U.L. 350° One-Hour Label – Fire and Impact Test Add 1 $\frac{1}{2}$ " to outside depth for dial and handle.



**Your Best Protection
Against Robbery**

Visit us online at
www.gardall.com
MADE IN THE U.S.A.

Firelined Gun Safes and Pistol Safe



Gardall Premium Quality Firelined Gun Safes

Keep Firearms
Protected
from the
Wrong Hands

Fire Tested to 1400°F
for 35 minutes
(Models 6024 & 6030)



GS2522-G-C

Model GS2522-G-C

- 1/8" Prime Steel Body
- 1/4" Prime Steel Door



PS915-B-E

Model PS915-B-E

- 3 Digit Electronic Lock
- Anchoring Plate

GF 5517 Features – Single Layer of Fire Protection

- 3-way locking bolts (5 active 1" bolts)
- 3-wheel lock with spyproof dial
- Burglary proof handle
- 4 anchoring holes
- Fire tested at 1100° F for 25 minutes
- 11 gun capacity
- Black powder coated paint
- Safe fits in standard closet

GBF 6024/6030 Features Double Layer of Fire Protection

- 3-way locking bolts (7 active 1½" bolts)
- U.L. Group II lock with spyproof dial
- Black powder coated paint
- 2 layers 5/8" U.L. rated fire board insulation
- U.L. Approved Intumescent door seal expands to 7X original size
- S&G electronic lock, add \$225 retail list
- 8 or 16 gun capacity (GBF 6024) or 14 or 18 gun capacity (GPF 6030)
- 3 spoke handle
- 4 anchoring holes
- Fire tested at 1400° F for 35 minutes

Model	Outside Dimensions			Inside Dimensions			Approx. Weight (lbs.)
	H	W	D	H	W	D	
PS915-B-E	4¼"	9½"	14"	3"	8"	9"	15
GS-2522-G-C	25"	22"	16¾"	24½"	21½"	13"	182
GF-5517-B-C	55¼"	17¾"	16"	53"	16"	11½"	300
GF-6024-B-C	59"	24"	22"	55"	21"	12½"	590
GF-6030-B-C	59"	30"	26"	55"	26¾"	20"	675

All Purpose Interior – 3 shelf interior available as an option. All specifications are subject to change without notice.



**Your Best Protection
Against Fire and Theft**

Visit us online at
www.gardall.com
MADE IN THE U.S.A.



Designed for complete protection of your valuables, a “B” rated burglary safe security welded inside a fire resistive safe.

Standard Features

- Class “B” Rated interior safe construction. Door of inner safe will interchange with other Gardall safes key lock or combination.
- Fire Resistive Exterior Safe – Insulated to withstand 1850°F for 2 hours.
- Finest Quality Combination Locks – U.L. listed Group II with built-in relocking device or key-op lock.
- Relocking Device – If back cover is knocked off of the lock, the independent relock device is activated, preventing bolt withdrawal.
- Boltwork Interior Door – Triple boltwork with independent relock device.
- Boltwork Exterior Door – Interlocking bolts extend into the safe walls, full length locking bar on hinge side of door to deter forcible entry by removal of hinges.
- Hard plate on both interior and exterior door.
- Available with electronic push-button lock.



Safe/Chest Combo

Model	Outside Dimensions				Inside Dimensions			Inside Cubic Inches	Appx. Wt. (lbs.)	Shelves
	H	W	D		H	W	D			
Z-1812/2	25"	17¼"	19¾"	MS	9¾"	11"	8"	1096	365	NA
				SS	7¾"	12"	10¾"	974		
Z-1818/2	25¾"	17¼"	25¾"	MS	9¾"	11"	14"	1828	455	NA
				SS	8"	12"	16¾"	1518		
Z-2218/2	29¼"	23¼"	25¾"	MS	12½"	17¼"	14"	3188	645	NA
				SS	9"	18"	16¾"	2198		
Z-3018/2	37¼"	23¼"	25¾"	MS	12½"	17¼"	14"	3188	740	2
				SS	17½"	18"	16¾"	5130		
Z-3620	45½"	25¾"	26¾"	MS	12½"	19½"	15¼"	4366	940	2
				SS	23¼"	20½"	18¾"	8937		
Z-4220	49½"	25¾"	26¾"	MS	12½"	19½"	15"	4366	1010	3
				SS	29¼"	20½"	18¾"	11243		
Z-4820	57½"	25¾"	26¾"	MS	12½"	19½"	15"	4366	1110	3
				SS	35¾"	20½"	18¾"	13550		

Standard colors: Gray or sandstone. Add 2" to outside depth for dial and handle.

Safe/Chest Combination - TL15 Money Safe/Two Hour Fire Safe

Model	Outside Dimensions				Inside Dimensions			Inside Cubic Inches	Approx. Wt. (lbs.)
	H	W	D		H	W	D		
SC-1120	39¼"	23¼"	25½"	Top	9"	12"	11"	1080	970
				Bottom	22"	18"	17½"	6460	
SC-1130	57½"	25¾"	28¼"	Top	11"	12"	11"	1080	1565
				Bottom	30½"	20½"	20"	12505	

Weights measured w/pallet. Shelves SC-1120 – 2, SC-1130 – 3. All specifications are subject to change without notice.



**Your Best Protection
Against Robbery and Fire**

Visit us online at
www.gardall.com



Gardall Safe Corporation has been manufacturing premium quality safes for home and office applications since 1950. Our Commercial High Security safes are manufactured to specifications which are more stringent than many of our competitors requirements. Some of the standard features on Gardall TL15 and TL30 safes are options with other manufacturers. Please be sure to compare our specifications with those of our competitors before making your decision.

- **TL15** – Tool Resistant for 15 minutes
- **TL30** – Tool Resistant for 30 minutes
- **TL30/6** – Tool Resistant for 30 minutes all six sides of safe.

Standard Features:

Door Construction:

- TL15 – 5" slab High Density Fiber Reinforced Material
- TL30 – 5" overall, 3" slab of High Density Fiber Reinforced Barrier Material – TDRII*
- TL30x6 – TL30x6 – 4½" overall thickness with 2" Defense Barrier

Body Construction:

- TL15 – 3" slab of High Density Barrier Material
- TL30 – 5" slab of High Density Barrier Material
- TL30x6 – 4½" thick composite Reinforced Manganese steel armor plate

Anti Burglary Components:

- Cross locking relockers.
- Punch resistant spindle handle and lock.
- Tempered glass reloading trigger.
- Bridge mounted lock.
- 1¼" chrome plated locking bolts.

Locks:

- Group II listed combination. Key lock available for dual custody.

Hinges:

- Massive heavy duty adjustable ball bearing hinges.

*TDR II – Special formulation of High Density Barrier Material with Fiber Reinforcement

	Model	Outside Dimensions			Inside Dimensions			Approx. Cubic Ft.	Approx. Weight	Shelves
		H	W	D	H	W	D			
TL-15	T15 1818	25"	25"	21½"	18"	18"	12"	1.8	930	1
	T15 2218	29"	25"	26"	22"	18"	16½"	3.8	1210	2
	T15 3822	45"	29"	29½"	38"	22"	20"	9.7	2095	3
	T15 5022	57"	29"	29½"	50"	22"	20"	12.7	2555	4
	T15 6222	69"	29"	29½"	62"	22"	20"	15.8	3015	5
TL-30	T30 1818	25"	25"	21½"	18"	18"	12"	1.8	950	1
	T30 2218	29"	25"	26"	22"	18"	16½"	3.8	1230	2
	T30 3822	45"	29"	29½"	38"	22"	20"	9.7	2145	3
	T30 5022	57"	29"	29½"	50"	22"	20"	12.7	2615	4
	T30 6222	69"	29"	29½"	62"	22"	20"	15.8	3090	5
	T30 7236	79"	43"	29½"	72"	36"	20"	30	4585	6
TL-30X6	T30X6 1818	25"	25"	21½"	18"	18"	12"	1.8	1105	1
	T30X6 3822	45"	29"	29½"	38"	22"	20"	9.7	2485	3
	T30X6 5022	57"	29"	29½"	50"	22"	20"	12.7	3025	4
	T30X6 6222	69"	29"	29½"	62"	22"	20"	15.8	3570	5
	T30X6 7236	79"	43"	29½"	72"	36"	20"	30	5225	6

TL30X6 Please call for quote



**Your Best Protection
Against Robbery**

Visit us online at
www.gardall.com



Gardall's new in-room safe has a durable powder coated finish and a superior electronic locking system. The highly reliable lock is a one-time use combination that is set by the user for each opening. Each lock has an electronic over ride code or a manual by-pass key (optional) to open lock if a combo is lost.

Standard Features

- Lock comes with audit trail feature
- 2 to 5 digit user code
- 3 bad codes puts lock in lock-out
- Easy-to-read LCD screen
- 4 holes in back for anchoring

Custom Sizes Available.

Please ask for a quotation.

Model	Outside Dimensions			Inside Dimensions			Shelves	Weight (lbs.)
	H	W	D	H	W	D		
GH4-T-E	10¼"	17¼"	14½"	7¼"	14¼"	11¼"	1	50

Add 1" to outside depth for handle.

Gardall Safe Corporation has been producing premium quality security products since 1950. Our safes will protect your important papers and valuables 24 hours a day, seven days a week.

You may have seen us on:


- *The Discovery Channel – “It Takes a Thief” Show*
- *The David Letterman Show*
- *The Today Show*
- *The Rosie O’Donnell Show*

You may have read about us in:

- *Time Magazine*
- *Money Magazine*
- *U.S. News and World Report*
- *Home Mechanix*
- *Consumer Digest Best Buy*
- *Reader’s Digest*
- *New York Magazine*

Custom Built Safes

Is the space you have available too small for our safes? Do you require additional **cladding** or **encasement**, **snorkles** and **chutes**, a **drop slot**, or a **rotary hopper**? If so, contact your authorized Gardall dealer, or contact our factory directly. (800) 722-7233.



Gardall Safe Corporation is not responsible for any typographical errors or mistakes in this catalog. Size and specifications are subject to change without notice.



Gardall
SAFE CORPORATION



Manufacturing Premium Quality Safes
Since 1950

